



Top Notch Signs & Graphics Ltd  
Unit D8 Heritage Business Park  
Heritage Way  
Gosport  
Hampshire  
PO12 4BG  
UK

Tel: 023 9252 0333

Email: [info@topnotchsigns.co.uk](mailto:info@topnotchsigns.co.uk)

Web: [www.topnotchsigns.co.uk](http://www.topnotchsigns.co.uk)

## Application Guide - Dry Application

1 - Position graphic or vinyl lettering complete with top paper and backing, roughly where it is required.

2- Hold in place with masking (or similar) tape.



3 - Adjust position until the text is level or exactly where required.



4 - Stick a strip of tape along the entire top edge.




5 - You can now cut the graphic into more manageable pieces, without it moving.



6 - Working on one section at a time, hinge the graphic section up on the masking tape and pull down the backing paper.

Be careful to ensure the actual vinyl graphic remains on the top application paper.



7 - With the backing paper removed gradually apply the graphic. Using a squeegee (or rag) apply pressure to the graphic in a side wards motion, gradually moving down until the vinyl has been stuck.



8 - Continue with the other sections of the graphic.

9 - Carefully remove the top application tape to leave only the vinyl.



10 - Any bubbles (*bubbles, what bubbles*) can be pricked with a pin and pressed down.

## Top Notch Graphics

### **Application Guide - Wet Application**

**Fill a spray bottle with clean water and add a few drops of washing up liquid. just enough to break the surface tension**

Wet application can be used in conjunction with the dry method described above

or

1 - Spray a generous film of the water solution on the surface.

2 - Remove backing from graphic and slap on.

3 - Adjust graphic to the desired position.

4- From the centre squeegee out the water.  
(using a plastic squeegee or piece of rigid card or plastic)

5- Allow to dry before removing application tape.